

Technical Data :-

Specifications	Plaster Grader	Ezee Premix-Internal	Ezee Premix-External
Sand Grade As per IS1542		2 - 3 mm particle size	3 - 4.5mm particle size
Binder		OPC grade Cement	OPC grade Cement
Colour		Light Grey	Light Grey
Strength		75-80kg/cm ²	75-80kg/cm ²
Density- Dry		1.8kg / Ltr	1.8kg / Ltr
Density – Wet		1.9 Kg / Ltr	1.9 Kg / Ltr
Workability		Easy	Easy
Coat Thickness		12 – 20mm	12- 20 mm
Coverage for 1mm thickness		1.3-1.5 kg/M ²	1.3-1.5 kg/M ²
Pot Time		60 mins	60 mins
Packing (bags)		40 kg	40 kg
Storage Life		6 months**	6 months**

Difference Between Conventional Plaster & Ezee Mix Plaster.:-

Conventional Plaster	EZEE MIX
Black Creek Sand Consist of Full Of Marsh, Mud & Silt.	Made By White Sand of Clean River washed, which is Completely Silt Free.
High Time Consumes for screening and washing the Sand.	No Wasting of Time in Screening & washing the Sand.
Mixing of Cement: Sand Ratio is Improper.	Mixed in Volumetric Batching Plant with Ideal Ratio.
Have to Add waterproofing Chemical.	EZEE MIX constaining International Standard Waterproofing Chemical.
Wastage Ratio of Cement & Sand is very High.	As It Is Pre - Mixed Bag Packing, No Wastage takes Place.
Requires More Area to Store Cement & sand.	Covers Less area to Stackle with Easy Handelling.
It's Very Difficult to Maintain the Mixing Ideal Mixing Ratio.	Ideally Mixed Ratio, as it is Ready Mixed, & Ready To Use.
Content Of Moisture is very High.	Its Absolutely Free From Moisture.
Coverage area is not Fixed.	Coverage per bag is Fixed.
Its Resulting High Shrinkage & Cracks.	It's Absolutely Free From Shrinkage & Cracks.
Less Workability.	High Workability.



Recons Group

Growth Is Passion.

Recons Group of Companies

● CEMENT ● BUILDING PRODUCTS ● INVESTMENTS

Swagat Bldg., 2nd Floor, Shradhhananad Road, Nr. Navin Thakkar Hall, Vile Parle (E), Mumbai – 57.

Tel .: 022- 40677000 / 26173045 | Fax : 022- 40677005 | E: info@recongroup.com | W: www.reconsgroup.com



Easy and Durable Plastering



Ezee Mix is a premium quality premixed cement based plaster with added waterproofing chemicals. Fast & Easy to use. Practically oracle tree, highly durable, water & weather resistant in all climatic conditions, intended to be used internally & externally for block & brick walls, ceiling of concrete surface as well as filling up as an ideal requirement of conventional Bond cement plaster.

Ezee Mix is manufactured from a specialized processed sand as IS1542 and it is a free from salts like sulphides, chlorides etc. This serves as a plaster coat of shrinkage free.