

* Fly Ash Content in Cement is

(%)

ACC

Wadi Cement Works



WORK TEST CERTIFICATE

Portland Pozzolana Cement

Test Certificate No. 16	5
Dated 21/05/19 Results Requirement as perior IS 1489 (Part I) : 201	5
Chemical Composition	5
Loss on Ignition (% by mass) Description Loss on Ignition (% by mass) Loss of Ignition (% by mass) Loss on Ignition	age 9 net
Magnesia (% by mass) 1.00 Not more than 6.0 % Sulphuric Anhydride SO3 (% by mass) 2.50 Not More than 3.5 % Chloride Content (% by mass) 0.02 Not more than 0.1 % for general pur more than 0.05 % for pre-stressed si Insoluble Residue (% by mass) 28.10 Not More than [X + 4.0 (100-X) / 100 Not less than (0.6 X), Where "X" is the Pozzolana content in cement Physical Analysis Fineness Blaine's Specific Surface Area (m² / kg) 332 Not Less than 300 Compressive Strength (MPa) 72 ± 1h (3 Days) 28.0 Not less than 16.0	age 9 net
Sulphuric Anhydride SO3 (% by mass) Chloride Content (% by mass) Chloride Residue (% by mass) 2.50 Not More than 3.5 % Not more than 0.1 % for general purmore than 0.05 % for pre-stressed signature than 0.05	and 9 not
Chloride Content (% by mass) O.02 Not more than 0.1 % for general purp more than 0.05 % for pre-stressed si Insoluble Residue (% by mass) Physical Analysis Fineness Blaine's Specific Surface Area (m² / kg) Compressive Strength (MPa) 72 ± 1h (3 Days) Not More than (0.1 % for general purp more than 0.05 % for pre-stressed si Not More than (0.6 X), Where "X" is the Pozzolana content in cement Not More than 0.1 % for general purp more than 0.05 % for pre-stressed si Not More than (0.6 X), Where "X" is the Pozzolana content in cement Physical Analysis 332 Not Less than 300 Compressive Strength (MPa) 72 ± 1h (3 Days) Not less than 16.0	ooo [©] not
Chloride Content (% by mass) 0.02 Not more than 0.1 % for general purmore than 0.05 % for pre-stressed signs and the pre-stressed signs are the pre-stressed signs and the pre-stressed signs are the pre-stress	ana ^o nat
Insoluble Residue (% by mass) 28.10 Not less than (0.6 X), Where "X" is the Pozzolana content in cement Physical Analysis 2 Fineness Blaine's Specific Surface Area (m² / kg) Compressive Strength (MPa) 72 ± 1h (3 Days) 28.10 Not less than (0.6 X), Where "X" is the Pozzolana content in cement Not less than (0.6 X), Where "X" is the Pozzolana content in cement 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Fineness Blaine's Specific Surface Area (m² / kg) 332 Not Less than 300	
Blaine's Specific Surface Area (m² / kg) Compressive Strength (MPa) 72 ± 1h (3 Days) 332 Not Less than 300 28.0 Not less than 16.0	
Blaine's Specific Surface Area (m² / kg) Compressive Strength (MPa) 72 ± 1h (3 Days) 332 Not Less than 300 28.0 Not less than 16.0	
72 ± 1h (3 Days) 28.0 Not less than 16.0	
3	
168 + 2h (7 Days) 38.2 Not less than 22.0	
30.2 Proceeds that 22.0	
672 ± 4h (28 Days) * 57.7 Not less than 33.0	
Setting Time (Minutes)	
4 Initial 150 Not less than 30	
Final 225 Not more than 600	
Soundness	
5 Le-Chatelier Expansion (mm) 0.50 Not more than 10.0	
Auto-Clave Expansion (%) 0.002 Not more than 0.8	
6 Drying Shrinkage (%)* Awaited Not more than 0.15	
Normal Consistency (%) 30.50	
Temp. During Testing (0 C) 27.00 $(27 \pm 2)^{0}$ C	

The above cement complies with the requirements of IS 1489 (Part I): 2015 for Portland Pozzolana Cement.

Manager (QA)

34.00