

## K LAKSHMI CEMENT Ltd.

## JAYKAYPURAM—307019 Dist. Sirohi, Rajasthan TEST CERTIFICATE FOR PORTLAND POZZOLANA CEMENT



## LICENCE NO. CM/L-1234838

WEEK No. 39

## **DATE OF ISSUE 07.10.2016**

CHEMICAL / PHYSICAL REQUIREMENTS	SPECIFICATION CLAUSE No.	REQUIREMENT AS PER IS No.1489(PART-I) – 1991 AMENDMENT No. 3	RESULTS OBTAINED
CHEMICAL REQUIREMENTS : #	6		
(i) Loss on ignition, percent by mass, Max. #	6.1	5.0	2.64
(ii) Magnesia, percentage by mass, Max #	6.1	6.0	2.32
(iii) Sulphuric Anhydride (SO <sub>3</sub> ), percent # by mass, Max	6.1	3.0	2.68
(iv) Insoluble Residue, percent by mass Max. #	6.1	4(100-x) x+	27.32
(v) Declared % of Fly Ash	5 & 9.1	100 (x=where x is the declare % age of Fly Ash) Not less than 15% and Not more than 35%	25+/-3
(vi) Chloride, percent by mass #	9.2	Not more than 0.1	0.044
PHYSICAL REQUIREMENTS:	7		
(i) FINENESS: SP. SURFACE	7.1	Not less than 300 m2/kg	349
(ii) SOUNDNESS : a) Le-chatelier method Expansion	7.2	Not more than 10 mm	1.00
b) Auto clave test expansion C.NO.T-0720		Not more than 0.8%	0.060
(iii) SETTING TIME	7.3		
a) Initial Setting time in Minutes		30 minutes, minimum	130
b) Final setting time in Minutes		600 minutes, maximum	180
(iv) COMPRESIVE STRENGTH 72 ± 1 Hours (3 Days)	7.4	16 Mpa, Min	30.0
168 ± 2 Hours (7 Days)		22 Mpa, Min	37.0
672 ± 4 Hours (28 Days) (v) Drying Shrinkage	7.5	33 Mpa, Min Not be more than 0.15%	Under Testing <b>Under Testing</b>

REMARKS: The test results complies with the requirements of IS: 1489(Part-I): 1991 for for all Chemical requirements and Physical requirements including Compressive Strength up to 7- days.

Compressive Strength up to 7- days.

# Not covered unde NABL Accreditation at present
Note: Results reported above are the average test results of all samples testing during relevant week.

CERTIFIED ISO 9001:2008 ISO 14001:2004 OHSAS 18001:2007

HOD(QC)

