

Certificate No. : TC - 8013



DASTAN, PALSANA, DIST. SURAT (GUJ.) LICENCE NO. CM/L-7200051895

## **TEST CERTIFICATE**



Customer Name & Address :

Sample Identification : Portland Pozzolana Cement (As per IS 1489 : Part 1 : 2015) Sample Date : 24.09.2019 to 30.09.2019 (Week No : 39) Certificate (ULR) No. : TC80131900000271P

Date of Issue: 09.10.2019


Sr. No	Particulars	Test Method	Requirement of IS:1489	Results Obtained
Chemical Requirements				
1	Loss on ignition(% by mass)	IS : 4032 - 1985	Not more than 5.0	2.13
2	Magnesia(% by mass)	IS : 4032 - 1985	Not more than 6.0	2.65
3	Sulphuric Anhydride (SO <sub>3</sub> )(% by mass)	IS : 4032 - 1985	Not more than 3.5	2.89
4	Insoluble Residue(% by mass)	IS : 4032 - 1985	4(100-x) x+ 100 (x=where x is the declare % age of Fly Ash)	24.22
5	Chloride(% by mass)*	IS : 4032 - 1985	Not more than 0.1	0.025
6	Declared % of Fly Ash (≤)	-	Not less than 15% and Not more than 35%	34.0
Mechanical Requirements				
1	Fineness (m²/kg)	IS : 4031 (Part-2) - 1999	Not less than 300	388
2	Normal Consistency (%)	IS : 4031 (Part-4) - 1988	-	33.25
3	Soundness : a) Le-chatelier expansion (mm) b) Autoclave test expansion (%)	IS : 4031 (Part-3) - 1988	Not more than 10 Not more than 0.8	0.5 0.054
4	Setting Time : a) Initial setting time (minutes) b) Final setting time (minutes)	IS : 4031 (Part-5) - 1988	Not less than 30 Not more than 600	135 190
5	Compressive Strength : a) 72 ± 1 Hours (3 Days) (MPa) b) 168 ± 2 Hours (7 Days) (MPa) c) 672 ± 4 Hours (28 Days) (MPa)	IS : 4031 (Part-6) - 1988	Not less than 16 Not less than 22 Not less than 33	28.3 37.6 Under Testing
6	Drying Shrinkage (%)	IS : 4031 (Part-10) - 1988	Not more than 0.15	Under Testing

Remarks : Results reported above are the average test results of all sample testing during the relevant week. \*: Not covered under NABL Accreditation at present.



**Technical Manager** 

Page 1 of 1



**Authorized Signatory** 

