

TEST CERTIFICATE

JSW

Ground Granulated Blast Furnace Slag

Sr. No.	Characteristic	Requirement as per BS:6699	Test Result
1	Fineness (M^2/KG)	275 (Min.)	381.00
2	Residue		
	Residue by wet sieve on 45μ (%)		3.95
3	Initial Setting Time (Min)	Not less than IST of OPC	205
4	Insoluble Residue (%)	1.5 (Max.)	0.28
5	Magnesia content (%)	14.0 (Max.)	7.96
6	Sulphide Sulphur (%)	2.00 (Max.)	0.52
7	Sulfate content (%) as SO_3	2.50 (Max.)	0.26
8	Loss on Ignition (%)	3.00 (Max.)	0.71
9	Manganese content (%)	2.00 (Max.)	0.22
10	Chloride content (%)	0.10 (Max.)	0.001
11	Moisture content (%)	1.00 (Max.)	0.01
12	Glass content (%)	67 (Min.)	94.95
13	Compressive Strength (N/mm^2)		
	After 7 days	12.0 (Min.)	18.63
	28 days	32.5 (Min.)	37.57
14	Chemical Moduli		
(A)	$CaO + MgO + SiO_2$	66.66 (Min.)	79.07
(B)	$CaO + MgO/SiO_2$	>1.0	1.27
(C)	CaO/SiO_2	<1.40	1.04

Note :There is No Indian Standard on GGBS. For reference BS specification is given.

Granulated slag used for JSW Steel Ltd.,GBS conforms to IS 12089:1987.

** COMPRESSIVE STRENGTH , SOUNDNESS AND INITIAL SETTING TIME ON BLEND OF 70% GGBS : 30% OPC.*

Week No.:	47	Month:	11	Year:	2015
-----------	----	--------	----	-------	------



Associate Vice President