



JSW PSC Cement

THE LEADERS, CHOICE

TEST CERTIFICATE

Portland Slag Cement as per IS 455:2015

REF.: JSW/QA/2021 6 DATE: 19-02-2021

WEEK NO.: 6 05-02-2021 11-02-2021

CHARACTERISTIC	RESULTS OBTAINED	REQUIREMENT OF IS 455:2015
(A) CHEMICAL COMPOSITION		
(i) Magnesia (MgO), % by mass	4.86	10.0 Maximum
(ii) Insoluble Residue, % by mass	0.39	4.0 Maximum
(iii) Sulphuric Anhydride (SO ₃) % by mass	2.23	3.5 Maximum
(iv) Sulphide Sulphur (S)	0.28	1.5 Maximum
(v) Loss on Ignition % by mass	0.80	5.0 Maximum
(vi) Total Chloride (Cl), % by mass	0.016	0.10 Maximum
(B) PHYSICAL TESTING		
1. Fineness of Cement		
Sp.Surface blaine (m²/kg)	365	225 m²/kg minimum
2. Soundness		
Le-Chatelier Expansion (mm)	1.00	10 mm Maximum
Autoclave Expansion (%)	0.057	0.8 % Maximum
3. Setting Time		
Initial (in Minutes)	180	Not less than 30 minutes
Final (in Minutes)	220	Not more than 600 minutes
4. Compressive Strength (MPa)		
(a) At 72 ± 1 Hrs.	29.28	16 MPa Minimum
(b) At 168 ± 2 Hrs.	39.52	22 MPa Minimum
(c) At 672 ± 4 Hrs.	Result Awaited	33 MPa Minimum

Remarks :

- 1. Temperature during testing $27 \pm 2^{\circ}$ c.
- 2. Portland Slag Cement conforms to the requirement of IS 455-2015 in all respects.
- 3. Specific Gravity 3.00 GGBS addition % 52 ± 2

Address:

JSW CEMENT LIMITED

Village- Khar Karavi, Post Office- Gadab

Taluka- Pen, District- Raigad

402107, Maharashtra. +91 2143 277601/2

Jushemm.

DGM - Quality