

KALBURGI CEMENT PVT. LTD.

<u>Corporate Office</u>: 8-2-626, Reliance Majestic Building, Road No. 10, Banjara Hills, Hyderabad – 500 034, A.P., India. Ph.: +91 40 3006999; Fax: +91 40 30006955

Works : Chatrasala (V), Kharchkhed (Post) - 585 320, Chincholi (Tq.), Gulbarga Dist.

+91 40 30006955 sholi (Tq.), Gulbarga Dist. CM

IS:269

41

TEST CERTIFICATE (OPC - 43 Grade)

Product : VICAT - PERFORMATE

Week No:

Despatched from: 07.10.2019 to 13.10.2019

| A. PHYSICAL REQUIREMENTS | | RESULTS | As per IS 269 – 2015 |
|----------------------------|---|---------|-------------------------------------|
| Fineness: | | | |
| a. | Specific Surface (m2/kg) | 265 | Not less than 225 |
| b. | Normal Consistency (%) | 29.50 | |
| Soundness: | | | |
| a. | By Le-Chatelier Method (mm) | 1.00 | Not more than 10 mm |
| b. | By Autoclave (%) | 0.056 | Not more than 0.8 % |
| Setting Time: | | | |
| a. | Initial Setting Time (minutes) | 180 | Not less than 30 |
| b. | Final Setting Time (minutes) | 275 | Not more than 600 |
| Compressive Strength (MPa) | | | |
| a. | 3 days | 35.92 | Not less than 23 |
| b. | 7 days | 45.32 | Not less than 33 |
| c. | 28 days | 57.36 | Not less than 43 & Not more than 58 |
| B. CHEMICAL REQUIREMENTS | | | |
| a. | Lime Saturation Factor | 0.89 | 0.66 - 1.02 |
| b. | Aluminum Modules | 1.10 | Not less than 0.66 |
| c. | Insoluble Residue (%) | 2.44 | Not more than 5.0 |
| d. | Magnesia (%) | 1.00 | Not more than 6.0 |
| e. | Sulphuric Anhydride (%) | 2.50 | Not more than 3.5 |
| f. | Loss on Ignition (%) | 2.58 | Not more than 5.0 |
| g. | Chlorides (%) | 0.030 | Not more than 0.1 |
| h. | Alkali Content (%) | 0.55 | Not more than 0.6 |
| i. | Temperature During Testing ⁰ C | 27.00 | 27 ± 2 |

T. S.M

Section In-Charge (Q.C)



Authorised Signature