

KALBURGI CEMENT PVT. LTD.

Corporate Office: 8-2-626, Reliance Majestic Building, Road No. 10, Banjara Hills, Hyderabad – 500 034, A.P., India. Ph.: +91 40 3006999; Fax: +91 40 3006955



IS:269

Works : Chatrasala (V), Kharchkhed (Post) - 585 320, Chincholi (Tq.), Gulbarga Dist.

TEST CERTIFICATE (OPC - 43 Grade)

Product: VICAT - PERFORMATE

Week No:

8

Despatched from: 17.02.2020 to 23.02.2020

| Despatched from: 17.02.2020 to 25.02.2020 | | | |
|---|---|---------|-------------------------------------|
| A. PHY | SICAL REQUIREMENTS | RESULTS | As per IS 269 – 2015 |
| Finenes | ss: | | |
| a. | Specific Surface (m2/kg) | 274 | Not less than 225 |
| b. | Normal Consistency (%) | 29.50 | |
| Soundness: | | | |
| a. | By Le-Chatelier Method (mm) | 1.00 | Not more than 10 mm |
| b. | By Autoclave (%) | 0.082 | Not more than 0.8 % |
| Setting Time: | | | |
| a. | Initial Setting Time (minutes) | 170 | Not less than 30 |
| b. | Final Setting Time (minutes) | 275 | Not more than 600 |
| Compressive Strength (MPa) | | | |
| a. | 3 days | 33.56 | Not less than 23 |
| b. | 7 days | 44.38 | Not less than 33 |
| C. | 28 days | Awaited | Not less than 43 & Not more than 58 |
| B. CHEMICAL REQUIREMENTS | | | |
| a. | Lime Saturation Factor | 0.91 | 0.66 – 1.02 |
| b. | Aluminum Modules | 1.20 | Not less than 0.66 |
| c. | Insoluble Residue (%) | 2.34 | Not more than 5.0 |
| d. | Magnesia (%) | 1.02 | Not more than 6.0 |
| e. | Sulphuric Anhydride (%) | 2.56 | Not more than 3.5 |
| f. | Loss on Ignition (%) | 2.82 | Not more than 5.0 |
| g. | Chlorides (%) | 0.030 | Not more than 0.1 |
| h. | Alkali Content (%) | 0.54 | Not more than 0.6 |
| i. | Temperature During Testing ⁰ C | 27.50 | 27 ± 2 |

17. of:1/2

Section In-Charge (Q.C)

Authorised Signature