

KALBURGI CEMENT PVT. LTD.

Corporate Office: 8-2-626, Reliance Majestic Building, Road No. 10, Banjara Hills, Hyderabad – 500 034, A.P., India. Ph.: +91 40 3006999; Fax: +91 40 30006955

Works : Chatrasala (V), Kharchkhed (Post) - 585 320, Chincholi (Tq.), Gulbarga Dist.

TEST CERTIFICATE (PPC)

Product : VICAT - DURAMATE

Week No:

Despatched from: 20.04.2020 to 26.04.2020

A. PHYSICAL REQUIREMENTS		RESULTS	As per IS 1489 (Part-1) 2015
Finenes	ss:		
a.	Specific Surface (m2/kg)	342	Not less than 300
b.	Normal Consistency (%)	32.50	
Soundness:			
a.	By Le-Chatelier Method (mm)	1.00	Not more than 10 mm
b.	By Autoclave (%)	0.036	Not more than 0.8 %
Setting Time:			
a.	Initial Setting Time (minutes)	170	Not less than 30
b.	Final Setting Time (minutes)	280	Not more than 600
Compressive Strength (MPa)			
a.	3 days	26.18	Not less than 16
b.	7 days	35.74	Not less than 22
C.	28 days	55.28	Not less than 33
d.	Drying Shrinkage(%)	0.014	Not more than 0.15
e.	Flyash Addition (%)	30.49	Not more than 35
B. CHEMICAL REQUIREMENTS			
a.	Insoluble Residue (%)	27.44	X+4(100-X)/100; X = % of Flyash
b.	Magnesia (%)	1.06	Not more than 6.0
c.	Sulphuric Anhydride (%)	2.28	Not more than 3.5
d.	Loss on Ignition (%)	2.16	Not more than 5.0
e.	Alkali Content (%)	0.54	Not more than 0.90
f.	Temperature During Testing(^O C)	28.00	27 ± 2

T. finz

Section In-Charge (Q.C)



Authorised Signature



17