







53 Grade Ordinary Portland Cement Despatched during Week No. 9-Jul-2022 28 From То 15-Jul-2022 Test Certificate No. 28 Reference No. WCW/IMS/QA/FM/17 Dated 23-Jul-2022 Requirement as per IS 269 : 2015 Results S.N. Parameters (Variety: OPC 53) Obtained **Chemical Composition** Lime Saturation Factor 0.92 Not greater than 1.02 and not less than 0.80 (CaO-0.7 *SO3) / (2.8* SiO2 + 1.2* Al2O3 + 0.65* Fe2O3) Ratio of % Alumina to that of Iron Oxide 1.28 Not less than 0.66 Al2O3 / Fe2O3 Insoluble Residue (% by mass) 1.34 Not more than 5.0 % 1 Magnesia (% by mass) 0.88 Not more than 6.0 % Sulphuric Anhydride (% by mass) 2.92 Not More than 3.5 % Total loss on Ignition (%) 2.02 Not More than 4.0 % Not more than 0.1 % for general purpose & not 0.010 Chloride Content (%) more than 0.05 % for pre-stressed structures **Physical Analysis** Fineness 2 Blaine's Specific Surface Area (m2 / kg) 314 Not Less than 225 **Compressive Strength (MPa)** 72 ± 1h (3 Days) 37.6 Not less than 27.0 3 47.6 Not less than 37.0 168 ± 2h (7 Days) 672 ± 4h (28 Days) * Awaited Not less than 53.0 Setting Time (Minutes) Initial 125 Not less than 30 4 Final 190 Not more than 600 Soundness 5 Le-Chatelier Expansion (mm) 1.00 Not more than 10.0 Auto-Clave Expansion (%) 0.060 Not more than 0.8 Normal Consistency (%) 26.75

The above cement complies with the requirements of IS 269 : 2015 (Variety: OPC 53) for 53 Grade Ordinary Portland Cement

27.00

(27 ± 2)0C

Manager (QA)

Temp. During Testing (0C)

6

DGM QC

Registered Office: Cement House, 121, Maharishi Karve Road, Mumbai - 400020